



TEKNOLOGISK
INSTITUT

Opsys 2.0 - Measured and predicted energy flexibility in a single family house

EUDP project

Ivan Katić, Teknologisk Institut



TEKNOLOGISK
INSTITUT

Opsys 2.0 Project

- Financial support by EUDP
- Running 2019-2023
- Total budget DKK 10 mill.
- Industrial partners: Bosch, Neogrid, Wavin
- R&D partners: Aalborg University, DTI
- Follow-up on the former Opsys project



Combined optimization of heat pumps and heat emitting systems

Energy and Climate

Søren Østergaard Jensen, Danish Technological Institute



TEKNOLOGISK
INSTITUT


Heat pump issues



- Forward temperature set too high
- No central control of valve opening
- Only simple means are available for HP override control
- Self consumption with PV power requires advanced control



Nettarif C (Radius)



TEKNOLOGISK
INSTITUT



Opsys 2.0 Project goals:

1. Develop a controller for heating, which combines both the heat source system and the emittent heat system. In this way we are able to **utilize the thermal mass of the building as a free storage** and also improve the efficiency of the heat pump.
2. Develop an algorithm with forecasting, taking into account the weather (Heat demand and PV production) and further the electricity prices. Hereby it should be possible to **lower the demand for buying expensive electricity in peak load hours**.
3. Demonstrate this in practice in an inhabited house, as well as in the laboratory, so that we can **gather operational experience** and optimise the control.



TEKNOLOGISK
INSTITUT

The Opsys 2.0 concept



TEKNOLOGISK
INSTITUT

Main activities


- Newly developed controller installed in a house in Kalundborg
- Batterydata from a house in Roskilde analyzed
- MPC controller developed
- Test rig at DTI refurbished
- Model for battery and PV implemented





TEKNOLOGISK
INSTITUT




Demo house in Kalundborg



TEKNOLOGISK
INSTITUT

Hardware

Preheat boks has Poul (som monteret)






TEKNOLOGISK
INSTITUT

Simulation: Forward temperature self-lowering algorithm


- Decreases forward temperature until the highest demanding room demand the valve to be continuously ON.
- Shuffles the PWM cycles for each valve to maintain constant flow
- Only an estimate of nominal flow is needed.



TEKNOLOGISK
INSTITUT

Test of the MPC (Kalundborg house)

- 24 h demand prognosis
- Hourly update
- Comparison with 97 days reference period: 11% savings






TEKNOLOGISK
INSTITUT

Here the house and floor has been
Precooled and is now ready for the
heating event

Here the future shows a heated floor

The trajectory ends up being a cooled floor

The house ends up being warm even
though no heat was produced



Here is an excessive heating period
being cancelled well in time

A planned heating period is being carried out




TEKNOLOGISK
INSTITUT

COP of the heat pump as a function of power uptake and temperature

$$\text{COP}_{\text{HP}} = \frac{k}{P_{\text{HP}}} + \left(\frac{k_0}{P_{\text{HP}}} + k_1 + k_2 P_{\text{HP}} \right) \text{COP}_{\text{CARNOT}} \quad (13)$$

with

$$\text{COP}_{\text{CARNOT}} \equiv \frac{T_F + 273.15 \text{ } ^\circ\text{C}}{T_F - T_a} \quad (14)$$





It has a cost to push HP output!

Dotted lines = original fit
Full lines = new best fit




TEKNOLOGISK
INSTITUT

Testrig at DTI



TEKNOLOGISK
INSTITUT


PI-diagram






TEKNOLOGISK
INSTITUT

Testrig: Results simple on/off charging on demand



TEKNOLOGISK
INSTITUT

Testrig: Results MILP battery controller





Main conclusions:

- Heat pumps can be disconnected during the electricity evening peak without loss of comfort in houses with concrete floor heating.
- In the low-energy test house in Kalundborg, efficiency was already quite good so savings were low. The saving rate was an estimated 11% over the test period of 97 days.
- The highest potential for energy savings is on relatively cold days with a high solar gain.
- Test results from the test rig at DTI show that the advanced control algorithm saves money (not energy) compared to simpler strategies. By implementing this one could save up to 20% on operational cost.
- There is still room for improvement and simplification of the control system. Most important, heat pumps should have an interface to allow external control of certain parameters such as the detected outdoor temperature. It is not a feasible solution to use “homemade” bypass control like in the current project.
- The system is most suitable for colder and sunny climates where there is a high heating demand during winter but also significant PV production to power a heat pump.